



## PH-ES06

型號



PH-ES尺寸表

材質: S45C

單位: mm

規格 NO	D	H	K	F	J	B	L	M	常規扭力 (N.m)	軸荷重 (KN)	輪測面壓 (N/mm <sup>2</sup> )	重量 (kg)
PH-ES6	6	19	21.5	8	10.5	13.5	16.5	M3	6.2	4	53	0.02
PH-ES8	8	22	25	10	13	17	21	M4	18	4.7	70	0.03
PH-ES9	9	23	26	10	13	17	21	M4	21	4.7	68	0.04
PH-ES10	10	24	27	10	13	17	21	M4	30	6.2	87	0.06
PH-ES11	11	25	28	10	13	17	21	M4	34	6.2	84	0.06
PH-ES12	12	26	29	10	13	17	21	M4	47	7.8	100	0.07
PH-ES13	13	27	30	10	13	17	21	M4	50	7.8	97	0.08
PH-ES14	14	31	34	12.5	16	21	26	M5	70	10	87	0.08
PH-ES15	15	32	35	12.5	16	21	26	M5	75	10	84	0.08
PH-ES16	16	33	36	12.5	16	21	26	M5	80	10	81	0.08
PH-ES17	17	34	37	12.5	16	21	26	M5	105	12.5	99	0.09
PH-ES18	18	35	38	12.5	16	21	26	M5	110	12.5	96	0.1
PH-ES19	19	47	56	17	22	28	34	M6	290	30	94	0.25
PH-ES20	20	47	56	17	22	28	34	M6	320	32	100	0.25
PH-ES22	22	47	56	17	22	28	34	M6	320	32	100	0.26
PH-ES24	24	50	59	17	22	28	34	M6	360	32	100	0.27
PH-ES25	25	50	59	17	22	28	34	M6	420	34	100	0.27
PH-ES28	28	55	64	17	22	28	34	M6	500	34	100	0.32
PH-ES30	30	55	64	17	22	28	34	M6	520	34	100	0.34
PH-ES32	32	60	69	17	22	28	34	M6	770	48	110	0.35
PH-ES35	35	60	69	17	22	28	34	M6	840	48	110	0.37
PH-ES38	38	65	74	17	22	28	34	M6	910	48	110	0.38
PH-ES40	40	65	74	17	22	28	34	M6	960	48	110	0.4
PH-ES42	42	75	84	20	25	33	41	M8	1000	65	110	0.63
PH-ES45	45	75	84	20	25	33	41	M8	1500	65	110	0.65
PH-ES48	48	80	89	20	25	33	41	M8	2000	85	140	0.68
PH-ES50	50	80	89	20	25	33	41	M8	2100	85	140	0.7
PH-ES55	55	85	91	20	25	33	41	M8	2500	95	140	0.73
PH-ES60	60	90	99	20	25	33	41	M8	2700	90	130	0.78
PH-ES65	65	95	104	20	25	33	41	M8	3200	100	140	0.83
PH-ES70	70	110	119	24	30	40	50	M10	4900	140	140	1.33
PH-ES75	75	115	124	24	30	40	50	M10	5300	140	130	1.4
PH-ES80	80	120	129	24	30	40	50	M10	5600	140	130	1.48
PH-ES85	85	125	134	24	30	40	50	M10	6700	160	130	1.55
PH-ES90	90	130	139	24	30	40	50	M10	7100	160	130	1.63
PH-ES95	95	135	144	24	30	40	50	M10	9100	195	135	1.7
PH-ES100	100	145	154	26	32	44	56	M12	10200	200	150	2.6
PH-ES110	110	155	164	26	32	44	56	M12	10600	200	150	2.8
PH-ES120	120	165	174	26	32	44	56	M12	13000	216	140	3
PH-ES130	130	180	189	34	40	54	64	M12	18900	290	135	4.6
PH-ES140	140	190	199	34	40	54	68	M14	20500	333	125	4.9
PH-ES150	150	200	209	34	40	54	68	M14	25000	362	120	5.2

